

HD30LV High Brightness Full HD 1080p Projector





- Bright 1080p projector 4500 ANSI lumens, perfect for brilliant big screen presentations
- 4K UHD Input and HDR Compatible
- Easy connectivity 2x HDMI, USB Power and built in speaker
- Portable and lightweight



The HD30LV is a compact Full HD 1080p lamp projector boasting a high brightness of 4500lm. This model is designed to be used in low to high ambient light environments for gaming, TV viewing, digital entertainment and other purposes, including home office. This projector features 4K and HDR input compatible, built-in speaker, rich cinematic color, and long lamp life with a low overall cost of ownership.

Specifications

Display/image	minary and subject to change without notice
Display technology	DLPTM
Resolution	1080p Full HD (1920x1080)
Brightness	4,500 lumens
Contrast ratio	22,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.38 ~ 91.15Khz
/ertical scan rate	50 ~ 85(120 for 3D)Hz
Jniformity	80%
Screen size	0.76m ~ 7.65m (29.93" ~ 301.14") diagonal
Lamp info	
_ight source type	Lamp
_amp watts	240
Lamp life hours (up to)	4000 (Bright), 15000 (Dynamic), 10000 (Eco)
Optical	
Throw ratio	1.5:1 ~ 1.66:1
Projection distance	1.1m - 10m / 43.31" - 393.7"
Zoom	1.1
Zoom type	Manual
Focal length	15.84 ~ 17.42
Native offset	116%
Connectivity Connections	
Connections	Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
General	
voise level (typical)	27dB
Noise level (max)	29dB
PC compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/////N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz), 4K UHD (24/30/50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Card Style Remote with CR2025 Coin Battery
Heat dissipation	1,023BTU/hour
Speaker count	1
Watts per speaker	3W
n the box	AC power cord
	Card Size Remote Control with CR2025 Coin Battery Basic user manual
nput lag	8.40ms
Optional wireless models	QuickCast Pro 4K KIT
Power	
ower supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (standby)	210W
Power consumption (min) Power consumption (max)	290W
Weight and dimensions	316 x 244 x 108 mm / 12.44" x 9.61" x 4.25"
Weight and dimensions Dimensions (W x D x H)	316 x 244 x 108 mm / 12.44" x 9.61" x 4.25" 3.9 kg / 8.6 lbs
Weight and dimensions	316 x 244 x 108 mm / 12.44" x 9.61" x 4.25" 3.9 kg / 8.6 lbs 2.88 kg / 6.35 lbs





Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 18052023085642